





No. 561

October 16, 1967

LUBRICATING OIL RECOMMENDATIONS

The following change in lubricating oil recommendations is being made for all Harley-Davidson 4-cycle motorcycles.

Use proper grade of oil for the lowest temperature expected before the next oil change period as follows:

| Use Harley-Davidson Oil | Use <u>Grade</u> | Air Temperature (Cold Engine Starting Conditions) |
|----------------------------|---------------------|---|
| Medium Heavy | 75 | Above 40° F. |
| Special Light | 58 | Below 40° F. |
| Regular Heavy | 105 | Severe Operating Conditions At High Air Temperatures |

The above recommendations reflect the trend toward lighter oils made possible through the development of better lubricating qualities. The lighter oils greatly improve ease of starting on motorcycles having kick starters.

Note: This bulletin is your authority to follow above new oil recommendations which supersede any previously published information in service manuals, handbooks or oil can labels.

HARLEY-DAVIDSON MOTOR CO.

Harley-Davidson, Inc. has given us permission to provide this document on our website for the sole purpose of helping us restore our motorcycles.

Harley-Davidson, Inc. retains copyright over these materials, and NO reproduction or other use of these materials is permitted without prior authorization from Harley-Davidson, Inc.

The **O**ld **S**portster and **K**-model **R**esearch **G**roup (OSKRG) is a group of individuals who have spent years researching the minute differences in the parts, fit, finish, and configuration of the Harley-Davidson 1952-1956 K-Models, and (early) 1957-1969 Sportster models.

The results of our research is published on our website www.harleyKmodel.com